

U.S. DEPARTMENT OF PATENT AND TRADEMARK OFFICE ATTORNEY'S DOCKET NUMBER

R 34231

TRANSMITTAL LETTER TO THE UNITED STATES  
DESIGNATED/ELECTED OFFICE (DO/EO/US)  
CONCERNING A FILING UNDER 35 U.S.C. 371

U.S. APPLICATION NO. (if known)

09/763762


INTERNATIONAL APPLICATION NO. PCT/DE 99/01389  
INTERNATIONAL FILING DATE May 8, 1999PRIORITY DATE CLAIMED  
August 27, 1998

## TITLE OF THE INVENTION

Method and Arrangement for Ensuring the Standstill of a Vehicle, especially in Combination with a Control of the Speed of the Vehicle

## APPLICANT(S) FOR DO/EO/US

Hermann Winner and Albrecht Irion



Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:

1. ☒ This is the **FIRST** submission of items concerning a filing under 35 U.S.C. 371.
2. ☐ This is the **SECOND** or **SUBSEQUENT** submission of items concerning a filing under 35 U.S.C. 371.
3. ☐ This express request to begin national examination procedures (35 U.S.C. 371(f) at any time rather than delay examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b) and PCT Articles 22 and 39(1).
4. ☒ A proper Demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date.
5. ☒ A copy of the International Application as filed (35 U.S.C. 371(c)(2))
  - a. ☒ is transmitted herewith (required only if not transmitted by the International Bureau).
  - b. ☐ has been transmitted by the International Bureau.
  - c. ☐ is not required, as the application was filed in the United States Receiving Office (RO/US).
6. ☒ A translation of the International Application into English (35 U.S.C. 371(c)(2))
7. ☐ Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3))
  - a. ☐ are transmitted herewith (required only if not transmitted by the International Bureau).
  - b. ☐ have been transmitted by the International Bureau.
  - c. ☐ have not been made; however, the time limit for making such amendments has NOT expired.
  - d. ☐ have not been made and will not be made.
8. ☐ A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).
9. ☒ An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)).
10. ☐ A translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)).

## Items 11. to 16. below concern other document(s) or information included:

11. ☒ An Information Disclosure Statement under 37 CFR 1.97 and 1.98.
12. ☒ An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.
13. ☒ A FIRST preliminary amendment.  
☐ A SECOND or SUBSEQUENT preliminary amendment.
14. ☐ A substitute specification.
15. ☐ A change of power of attorney and/or address letter.
16. ☒ Other items or information:
  1. Four (4) sheet(s) of drawing.
  2. Form PCT/RO/101
  3. Form PCT/ISA/210
  4. Form PCT/ISA/220
  5. Form PCT/IPEA/401

097763762

PCT/DE 00/01389

R 34231

17. ☒ The following fees are submitted:

**Basic National Fee (37 CFR 1.492(a)(1)-(5)):**

Search Report has been prepared by the EPO or JPO.....\$860.00

International preliminary examination fee paid to USPTO (37 CFR 1.482).....\$670.00

No international preliminary examination fee paid to USPTO (37 CFR 1.482) but international search fee paid to USPTO (37 CFR 1.445(a)(2)).....\$760.00

Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2) paid to USPTO.....\$970.00

International preliminary examination fee paid to USPTO (37 CFR 1.482) and all claims satisfied provisions of PCT Article 33(2)-(4).....\$96.00

CALCULATIONS PTO USE ONLY

\$860.00

**ENTER APPROPRIATE BASIC FEE AMOUNT =**

\$860.00

Surcharge of **\$130.00** for furnishing the oath or declaration later than ☐ 20 ☐ 30 months from the earliest claimed priority date (37 CFR 1.492(e)).

Claims	Number Filed	Number Extra	Rate
Total Claims	5 - 20 =	0	X \$18.00
Independent Claims	2 - 3 =	0	X \$80.00
Multiple dependent claim(s) (if applicable)			+ \$270

**TOTAL OF ABOVE CALCULATIONS =**

\$860.00

Reduction by 1/2 for filing by small entity, if applicable. Verified Small Entity Statement must also be filed. (Note 37 CFR 1.9, 1.27, 1.28).

**SUBTOTAL =**

\$860.00

Processing fee of **\$130.00** for furnishing the English translation later than ☐ 20 ☐ 30 months from the earliest claimed priority date (37 CFR 1.492(f)).

**TOTAL NATIONAL FEE =**

\$860.00

Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31). **\$40.00** per property +

**TOTAL FEES ENCLOSED =**

\$860.00

Amount to be:  
refunded  
charged

- a. ☒ A check in the amount of \$860.00 to cover the above fee is enclosed.
- b. ☐ Please charge my Deposit Account No. 15-0773 in the amount of \$860.00 to cover the above fees. A duplicate copy of this sheet is enclosed.
- c. ☒ The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No. 15-0773. A duplicate copy of this sheet is enclosed.

**Note: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137(a) or (b) must be filed and granted to restore the application to pending status.**

SEND ALL CORRESPONDENCE TO:

Walter Ottesen  
Patent Attorney  
P.O. Box 4026  
Gaithersburg, Maryland 20885-4026



SIGNATURE

Walter Ottesen

NAME

25,544

REGISTRATION NUMBER

In the United States Patent and Trademark Office

In re patent application of: Hermann Winner and  
Albrecht Irion

International Application No: PCT/DE 99/01389 filed on  
May 8, 1999

Priority Claimed: German patent application 198 38 885.3  
filed on August 27, 1998

Title of Invention: Method and Arrangement for Ensuring the  
Standstill of a Vehicle, especially in  
Combination with a Control of the Speed of  
the Vehicle

Attorney Docket: R 34231

Preliminary Amendment

Honorable Commissioner of  
Patent and Trademarks  
Washington, D. C. 20231

Dear Sir:

Please amend the above-identified application as delineated  
below.

In the Disclosure:

On page 1, please delete line 5 and insert the following:

-- Field of the Invention --.

On page 1, between lines 8 and 9, please insert the  
following:

-- Background of the Invention --.

On page 2, please delete line 27 and insert the following:

-- Summary of the Invention --.

On page 4, please delete line 5 and insert the following:

-- Brief Description of the Drawings -

On page 4, please delete line 21 and insert the following:

-- Description of the Preferred Embodiments of the Invention --.

On page 12, lines 6, please delete "4b" and substitute

-- 4d -- therefor.

In the Abstract:

On page 16, please delete lines 1 to 3 and substitute  
therefor:

-- Abstract of the Disclosure --.

On page 16, please delete line 12.

In the Claims:

Please cancel claims 1 to 7 and add claims 8 to 12 as  
follows:

8. A method for ensuring standstill of a vehicle in combination  
with a speed control of the vehicle, the method comprising the  
steps of:

braking a vehicle to standstill with a controller of said  
vehicle;

building up and/or maintaining a braking force in the manner

of a parking brake function which is again reduced with a start-drive command of the driver; and,

interrupting the force flow in the drive train of said vehicle by controlling an automatic transmission into a neutral position or a park position.

9. The method of claim 8, comprising the further step of maintaining the parking brake braking force even when the supply voltage for the electrical systems of the vehicle is switched off.

10. The method of claim 8, comprising the further step of maintaining the neutral position or the park position of the transmission when the supply voltage for the electrical systems of the vehicle is switched off; and, only then leaving the position of the transmission when a start-drive command of the driver is recognized.

11. The method of claim 8, comprising the further step of interrupting the force flow after a predetermined time has elapsed after detection of standstill.

12. An arrangement for ensuring standstill of a vehicle, the arrangement comprising:

a speed controller for braking said vehicle to standstill;

means for detecting said standstill;

means for building up and/or maintaining a braking force in the sense of a parking brake;

means for again reducing said braking force when a  
start-drive command of the driver is detected; and,

transmission control means for controlling an automatic  
10 transmission into the neutral position or the park position while  
interrupting the force flow in the drive train to ensure said  
standstill of said vehicle.

Remarks

Claims 8 to 12 have been added and claims 1 to 7 are cancelled so that claims 8 to 12 are pending in this application of which claims 8 and 12 are in independent form. The new claims make improvements as to the form of the original claims.

The disclosure has been amended to add appropriate headings and to make needed corrections.

Respectfully submitted,



Walter Ottesen  
Reg. No. 25,544

Walter Ottesen  
Patent Attorney  
P.O. Box 4026  
Gaithersburg, Maryland 20885-4026

Phone: (301) 869-8950

Date: February 27, 2001

4 | PRTS

Attorney Docket No: R 34231

Method and Arrangement for Ensuring the Standstill of a Vehicle,  
especially in Combination with a Control  
of the Speed of the Vehicle

5 State of the Art

The invention relates to a method and an arrangement for ensuring the standstill of a vehicle, especially in combination with a control of the speed of the vehicle.

10 A method and an arrangement for ensuring the standstill of a vehicle is known, for example, from EP 375 708 B1 (US-Patent 5 129 496). There, the standstill of the vehicle is derived on the basis the wheel speed signals whereupon a braking force is built up at at least one of the wheel brakes in the sense of a parking brake function. This parking brake function is, however, switched off when the driver switches off the  
15 voltage supply for the vehicle control systems. A certainty as to standstill is therefore only guaranteed when the supply voltage is switched on.

20 It is a task of the invention to provide measures which ensure the standstill of a vehicle for each case.

The SAE paper number 96 10 10 (Adaptive Cruise Control, System Aspects and Development Trends, 1996, by Hermann Winner, Stefan Witte, Werner Uhler and Bernd Lichtenberg) shows a speed control while considering the distance to the vehicle traveling  
25 ahead. Here, the driver inputs the desired speed of the vehicle via an operator-controlled lever with the usual functions of road speed controllers. This desired speed is controlled comparable to a conventional road speed controller when there is no vehicle present ahead. A desired acceleration is computed from the  
30 difference between the desired speed and the driving speed and



this acceleration is made available for controlling the drive unit of the vehicle. If a radar system detects a vehicle traveling ahead, then the distance and relative speed to this vehicle are determined. The control task comprises to control  
5 the relative speed to zero and, simultaneously, maintain a speed-dependent desired distance. Parameters for determining the desired distance can be set by the driver. This so-called follow-on controller likewise determines a desired acceleration from the above-mentioned quantities. The desired acceleration values can also be negative so that they correspond to  
10 deceleration desired values. These are adjusted by influencing the engine of the vehicle and/or the brakes.

Correspondingly, DE-A 43 38 399 shows a road speed controller which inputs a desired acceleration of the vehicle on the basis of the difference between the desired and actual  
15 speeds. This desired acceleration is adjusted by controlling the engine and/or by actuating the wheel brakes of the vehicle.

In road speed controller systems of this kind, it can happen that the vehicle is braked to standstill. Here too, it is  
20 necessary to make available a guarantee of this standstill.

From German patent application 197 03 688, a procedure is known with the aid of which a comfortable braked stopping of the vehicle is made possible. The braking force at the wheels is reduced somewhat in order to reduce the stopping jolt when there  
25 is a drop of a specific vehicle speed in the region of the standstill speed.

#### Advantages of the Invention

The solution in accordance with the invention makes available a safeguard as to standstill which remains active even  
30 after the supply voltage is switched off. An unintended release

of the standstill latching is thereby precluded. The use of a parking brake having an electromotoric actuator is especially advantageous. The actuator then remains in the position assumed at the end of its driving and is only brought back to its start position by a renewed, releasing drive signal. Correspondingly, a parking brake can be provided which is actuated on a hydraulic or pneumatic basis. In this parking brake, the controlled pressure means is latched and the braking action is maintained and only released when there is a releasing drive signal.

It is especially advantageous that the standstill safeguard is only released when the driver inputs a corresponding drive command by actuating the operator-controlled element.

The connection of this standstill safeguard function with a road speed controller is of special advantage, especially with the initially mentioned adaptive road speed controller which can brake the vehicle to standstill. At least after a predetermined time after reaching standstill, the standstill is ensured by the automatic latching of a parking brake. Switching off the supply voltage does not lead to an unintentional release of the assurance.

In vehicles having an automatic converter transmission and when the parking brake is actuated at standstill, it is of special advantage, for reducing the consumption of fuel, that the transmission is controlled to the neutral position or a controllable clutch is interrupted in order to interrupt the force flow between the drive unit and the vehicle wheels.

It is especially advantageous when the transmission automatic for the standstill safeguard is controlled into the park position after the standstill of the vehicle. This can be carried out for interrupting the force flow or also as a

substitute for the parking brake to ensure the standstill of the vehicle. Here, this position, as in the case of the parking brake, is retained in an advantageous manner when the supply voltage is switched off.

## Drawing

The invention will be explained in greater detail in the following with respect to the embodiments shown in the drawing. FIG. 1 shows an overview circuit diagram of a control unit for controlling the speed of a vehicle which is explained in greater detail in FIG. 2 with respect to an example of an adaptive road speed controller. FIG. 3 shows the solution of the invention with respect to a flowchart which sketches a program which runs in a microprocessor of the control unit. FIG. 4 shows time diagrams on the basis of which a preferred realization of the solution of the invention is shown. In addition to the application in the preferred embodiment for an adaptive road speed controller, the illustrated solution is also used in all areas of application in which the vehicle is guided into standstill, for example, on the basis of a brake pedal actuation of the driver, of other automatic braking operations, et cetera.

## Description of the Embodiments

The solution of the invention is described hereinafter based on the preferred application of an adaptive road speed controller without this embodiment limiting the area of application of the described solution as mentioned above.

FIG. 1 shows an overview circuit diagram of a control unit 10 for an adaptive road speed controller. The control unit 10 includes an input circuit 12, at least one microcomputer 14 and an output circuit 16. These elements are connected to each other via a communication system 18 for

exchanging data and information. The following are connected to the input circuit 12: input lines 20 from a measuring device 22 for detecting the road speed; an input line 24 from an operator controlled element 26, which is actuatable by the driver, for inputting the operating state of the road speed controller and the desired distance; and, an output line 28 from a distance measuring unit 30, preferably a radar apparatus. Furthermore, additional input lines 32 to 34 from measuring devices 36 to 38 for detecting additional operating quantities of the vehicle are connected to the input circuit 12. These operating quantities are used in the adaptive road speed control. Such operating quantities are, for example, steering angle, transverse acceleration, et cetera. The control unit 10, there the at least one microcomputer 14, influences the power of the drive unit of the vehicle in the context of the adaptive road speed control via at least one output line 40 and corresponding actuating devices 42 (for example, electronic engine control apparatus). In a preferred embodiment, the control unit 10 influences the braking force at the wheel brakes of the vehicle via the output line 44 and corresponding actuating elements 46 (for example, of a braking system with ABS/ASR elements). In a preferred embodiment, a control unit 50 for controlling an automatic transmission and/or an electrically controllable clutch are driven via an output line 48.

The basic principle of the adaptive road speed control, which is known from the state of the art initially mentioned herein, is presented in FIG. 2 with respect to a sequence diagram which shows the basic interrelationships for the adaptive road speed control. The realization of the road speed control takes place in the preferred embodiment as a program of the

microcomputer 14 via which the interrelationships shown in FIG. 2 are realized.

The illustrated adaptive road speed controller has two basic functions, namely, the road speed controller 100 and the distance controller 102. The difference  $\Delta V$  between the desired speed  $V_{des}$  and the actual speed  $V_{act}$  is supplied from a comparator position 104 to the road speed controller 100 realized in a conventional manner. The desired speed  $V_{des}$  is determined in dependence upon the operating state of the operator-controlled element 21 in a selection stage 106. Thus, for example, in the operating state "set", the current actual speed value is assumed as the desired speed and, in the operating state "acceleration", ramps of the desired speed, which change as a function of time, are pre-given, et cetera. The output signal  $desF$  is formed by the road speed controller 100 in dependence upon the speed difference in accordance with a pre-given control strategy (for example, PD control). The output signal  $desF$  is outputted to a switching element 108 and via the line 107 to the controller 102.

Depending upon the switch position, the switching element conducts the output signal  $desF$  of the road speed controller or the output signal  $desD$  of the distance controller to a selection stage 110. The selection stage forms a control signal, which is dependent upon the supplied output signal, for influencing the engine power (output line 40) or the braking force (output line 44). The distance control includes a selection stage 112 which determines the relevant vehicle which is to be used as a forward vehicle for distance control in dependence upon: the radar signals supplied via the input line 28; the actual speed; and other quantities supplied via the lines 32 to 34. These quantities include, for example, steering angle, yaw rate and

acceleration of the vehicle. The course of the vehicle, which is to be expected, is determined based on the speed and the steering angle and/or the yaw rate. The radar sensor supplies the distance to the detected objects, the relative speed thereof and the angle to the various objects so that the relevant vehicle is selected from a comparison of the supplied data with the course of the vehicle which is to be expected in the future. Then, the values determined by the radar sensor for the spacing to the relevant vehicle  $D_{act}$  and its relative speed  $V_{rel}$  are outputted.

The actual distance is supplied to a comparison stage 114 wherein the difference between the desired distance  $D_{des}$ , which is pre-given by the driver, and the determined actual distance is formed and supplied to the distance controller 102. The relative speed is transmitted to the distance controller 102 from the selection stage 112. The desired distance to the relevant forward traveling vehicle is determined in a selection stage 116 in dependence upon an actuating signal of the driver and the actual speed which fixes the desired time interval to the forward traveling vehicle in seconds. The distance controller 102 forms an output signal  $desD$  with which the distance difference as well as the relative speed of the forward traveling vehicle is brought toward zero. The output signal  $desD$  is supplied to the switching element 108. The switching element is switched over into the position shown in phantom outline when a forward traveling vehicle has been detected to which the distance is to be adjusted. This means that the road speed controller 100 determines engine power and brake power in accordance with its input quantities when no vehicle has been determined for distance control, whereas, for a detected forward traveling vehicle, the distance controller 102 controls engine power and brake power.

The selection stage 110 decides whether the engine control or the braking control is activated in dependence upon the supplied desired value which essentially corresponds to a desired acceleration or deceleration. If a reduction of the engine power to maintain the desired deceleration is insufficient, then the brakes are activated; otherwise, the deceleration control is carried out via a control of the engine power.

To improve the use for the driver, it is desirable that a road speed controller of this kind can brake the vehicle to standstill. For this reason, a standstill detection 113 is provided in accordance with FIG. 2 which determines, at least on the basis of the road speed actual signal VACT, the standstill of the vehicle as well as an operational state which lies directly ahead of the standstill of the vehicle. If the standstill detection 113 determines (for example, via a drop below a pregiven speed limit value) that the vehicle is in the region of standstill, then a corresponding piece of data is outputted to the selection stage 110. In this case, the brake system is controlled via the output line 44, for example, as in the initially mentioned state of the art for controlling the stopping braking operation. If the standstill detection 113 recognizes (for example, on the basis of an extrapolated speed) the standstill of the vehicle, then a corresponding piece of data is again outputted to the selection stage 110 which leads to the condition that, via the line 44, the braking force at the wheel brakes is built up in the sense of a parking brake function. In a preferred embodiment, this parking brake function is realized by means of an electromotoric actuator operating on at least one wheel brake. The actuator brings friction pads in contact for braking the vehicle and the actuator remains in the assumed

position at the ending of the drive, that is, the actuator is  
latched and the actuator is only brought into its initial  
position via a renewed releasing drive signal. In another  
embodiment, a wheel brake is actuated on a hydraulic or pneumatic  
base in the sense of a parking brake function, wherein the  
5 pressure medium is locked in, the braking action is maintained  
and is only released with a releasing drive signal. In a further  
solution, the parking brake is actuated via a brake cable. The  
brake element is pretensioned via a reset device in the parking  
brake applied position in which friction linings are in contact  
10 for braking. From this position, the parking brake is  
electrically, hydraulically or pneumatically released. The  
parking brake is automatically tensioned by the reset device when  
switching off this actuation.

15 Additionally, or alternatively to the brake force buildup in  
the sense of a parking brake, a corresponding datum is outputted  
to the transmission control via the line 48 when a standstill of  
the vehicle is detected. The transmission control triggers a  
switching of the transmission into the neutral position or into  
20 the park position. The switching of the transmission takes place  
in a preferred embodiment after a specific time after detecting  
standstill of the vehicle. A signal is furthermore applied to  
the standstill detection 113 via at least one of the lines 32  
to 34. This signal represents a start-drive command of the  
25 driver. A signal of this kind can, for example, be a position  
signal of an accelerator pedal, an output signal of a switch (for  
example, of a road speed controller switch) or of a switch of an  
adaptive road speed controller. If the standstill detection 113  
detects a corresponding start-drive command of the driver, then a  
30 corresponding datum is outputted to the selection stage 110 or to



the transmission control which again releases the parking brake, that is, the park position of the transmission for ensuring standstill. What is essential is that even after a drop in the supply voltage for the control units (drive switch off) the parking brake and/or the park position of the transmission remains latched so that it is ensured that there is no unintended releasing of the function which ensures the standstill of the vehicle.

In the preferred embodiment, the solution according to the invention is realized as a program of a microcomputer. An example of such a program is described with respect to the flowchart of FIG. 3. This program is run through at pregiven time intervals when the supply voltage is switched on.

In a first step 150, a check is made as to whether a driver command to start driving the vehicle is present. In the preferred embodiment, this start driving command is determined on the basis of a quantity, which represents the position of the accelerator pedal, when the accelerator pedal is deflected from a release state into an actuated state. In addition, switching signals can be provided which signalize a start drive command. For example, switching elements activate an adaptive or a conventional road speed controller. The consideration of the clutch lever position signals and transmission lever position signals is likewise advantageous in some embodiments. If no such start drive command is present, a check is made in step 152 as to whether the adaptive road speed controller ACC is active. If this is not the case, then the program of FIG. 3 is ended and is run through anew at pregiven times. If step 152 yields that the adaptive road speed controller is active, then, in step 154, a check is made as to whether the vehicle is at standstill. This

is carried out on the basis of an extrapolation of the speed trace as in the state of the art. If this is not the case, then a check is made in accordance with step 156 as to whether the road speed has dropped below a specific limit value, that is, whether the vehicle is on the way to standstill. If this is not the case, then, according to step 158, the initially described control is carried out in the context of an adaptive road speed controller (ACC); otherwise, a stopping function is initiated as described in the state of the art. If step 154 yields that the vehicle is at standstill, then, according to step 162, a braking force is built up at at least one of the wheel brakes in order to provide preparation of a parking brake function or an electrically controllable parking brake is actuated and, if required, the transmission is switched into the neutral position after a predetermined time. In lieu of the neutral position or in an advantageous embodiment, the transmission is switched into the park position when standstill is detected. Furthermore, the adaptive road speed controller is switched off. The subprogram is ended after the steps 162, 160 or 158 and then repeated at a pregiven time. If step 150 has yielded that a start drive command is present, then, according to step 164, the parking brake is released and/or the park position or neutral position of the transmission is disabled. Thereafter, the program continues with step 152.

If, after step 162, the supply voltage for the control unit is switched off, then the parking brake and/or the park position of the transmission is latched until a start drive command of the driver is detected in accordance with step 150 after the supply voltage is switched on again. In this way, standstill is guaranteed which would not lead to an unintended release of the

parking brake and/or of the park position of the transmission.

The operation described with respect to FIG. 3 is made clearer on the basis of the time diagrams of FIG. 4. FIG. 4a shows the time trace of the road speed VFZ and FIG. 4b shows the time-dependent trace of the supply voltage U and FIG. 4c shows the time-dependent trace of the parking brake force FFB. FIG. 4b shows a signal which represents the state of the transmission especially whether the transmission has assumed the park or neutral position; whereas, FIG. 4e shows a two-value signal which represents the presence of a start drive command AW.

An operating situation is assumed wherein the vehicle is braked until standstill. This can take place either via a road speed controller as described in the preferred embodiment or via a corresponding brake actuation of the driver. At time point T0, the road speed (see FIG. 4a) could have dropped so far that the standstill of the vehicle is detected. Accordingly, at time point T0, a parking brake force is built up in accordance with FIG. 4c. In one embodiment, after an elapse of a specific time, the transmission is switched into the neutral position or the park position at time point T1 in accordance with FIG. 4d. In another embodiment, the park position of the transmission is assumed immediately at time point T0 or the park position is switched at time point T0 in lieu of the parking brake force buildup. At time point T2, the supply voltage U of the control unit is switched off (see FIG. 4b). The parking brake force and the transmission state are maintained (see FIG. 4c, FIG. 4d). At time point T3, the supply voltage is again switched on. A start drive command is detected at time point T4 so that there is a movement out of the transmission state and/or the parking brake force is reduced. The parking brake force drops to zero, the



## Patent Claims

1. Method for making certain as to the standstill of a vehicle, especially in combination with a control of the speed of the vehicle, wherein a braking force is built up in the sense of a parking brake function when the standstill of the vehicle is detected and wherein the force is again reduced when there is a start drive command of the driver, characterized in that the parking brake force is maintained when the supply voltage for the electrical systems of the vehicle is switched off.

2. Method for making certain as to the standstill of a vehicle, especially in combination with a control of the speed of the vehicle, wherein the standstill of the vehicle is detected and measures are taken to make certain as to the standstill, characterized in that these measures comprise switching an automatic transmission into the park position.

3. Method of claim 2, characterized in that the park position of the transmission is maintained when the supply voltage for the electrical systems of the vehicle is switched off and a movement out of the park position only then takes place when a start drive command of the driver is detected.

4. Method of one of the above claims, characterized in that the speed control of the vehicle is an adaptive road speed controller which brakes the vehicle until standstill.

5. Method of claim 1, characterized in that, preferably, the force flow in the drive train is interrupted after the elapse of

a predetermined time, especially, the automatic transmission is controlled into the neutral position or the park position.

6. Arrangement for making certain of the standstill of a vehicle, especially in combination with the control of the speed of the vehicle, the arrangement having standstill detection means which detect a standstill of the vehicle and having brake force control means which build up a brake force in the sense of a parking brake when standstill is detected and which again reduce the brake force with a detection of the start drive command of the driver, characterized in that means are provided which maintain the parking brake force also when the supply voltage for the electrical systems of the vehicle is switched off.

7. Arrangement for making certain of the standstill of a vehicle, especially in combination with a control of the speed of the vehicle, the arrangement having standstill detection means which detect the standstill of the vehicle and having means which initiate measures for making certain of the standstill of the vehicle, characterized in that the means for making certain of the standstill switch an automatic transmission into the park position.

Method and Arrangement for Ensuring the Standstill of a Vehicle,  
especially in Combination with a Control of the Speed of the  
Vehicle

A method and an arrangement for ensuring the standstill of a  
5 vehicle, especially in combination with a control of the speed of  
the vehicle, are suggested, wherein a braking force is built up  
to realize a parking brake when standstill of the vehicle is  
detected and/or a transmission is switched into the park  
position. The brake force or the transmission position is also  
10 maintained when the supply voltage for the electrical systems of  
the vehicle is switched off.

(FIG. 3)

PCT

WELTORGANISATION FÜR GEISTIGES EIGENTUM  
Internationales Büro

INTERNATIONALE ANMELDUNG VERÖFFENTLICHT NACH DEM VERTRAG ÜBER DIE  
INTERNATIONALE ZUSAMMENARBEIT AUF DEM GEBIET DES PATENTWESENS (PCT)



(51) Internationale Patentklassifikation <sup>7</sup> :

B60T 8/00

A2

(11) Internationale Veröffentlichungsnummer: WO 00/12365

(43) Internationales

Veröffentlichungsdatum:

9. März 2000 (09.03.00)

(21) Internationales Aktenzeichen:

PCT/DE99/01389

(22) Internationales Anmeldedatum:

8. Mai 1999 (08.05.99)

(30) Prioritätsdaten:

198 38 885.3

27. August 1998 (27.08.98)

DE

(71) Anmelder (für alle Bestimmungsstaaten ausser US): ROBERT BOSCH GMBH [DE/DE]; Postfach 30 02 20, D-70442 Stuttgart (DE).

(72) Erfinder; und

(75) Erfinder/Anmelder (nur für US): WINNER, Hermann [DE/DE]; Im Mehl 3, D-76229 Karlsruhe (DE). IRION, Albrecht [DE/DE]; Schaedleweg 2, D-70563 Stuttgart (DE).

(81) Bestimmungsstaaten: JP, US, europäisches Patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).

Veröffentlicht

Ohne internationalen Recherchenbericht und erneut zu veröffentlichen nach Erhalt des Berichts.

(54) Title: METHOD AND DEVICE FOR SECURING THE STANDSTILL OF A VEHICLE, NOTABLY IN CONJUNCTION WITH A VEHICLE SPEED CONTROL


(54) Bezeichnung: VERFAHREN UND VORRICHTUNG ZUR SICHERSTELLUNG DES STILLSTANDES EINES FAHRZEUGS, INSBESONDERE IN VERBINDUNG MIT EINER STEUERUNG DER GESCHWINDIGKEIT DES FAHRZEUGS

(57) Abstract

The invention relates to a method and a device for securing the standstill of a vehicle, notably in conjunction with a control of vehicle speed. After the vehicle has been recognized as standing still, a braking power for a parking brake is generated and/or a transmission is shifted into the parking position. The braking power and/or position of the transmission are maintained even when the supply voltage for the electrical systems of the vehicle has been switched off.


(57) Zusammenfassung

Es werden ein Verfahren und eine Vorrichtung zur Sicherstellung des Stillstandes eines Fahrzeuges, insbesondere in Verbindung mit einer Steuerung der Geschwindigkeit des Fahrzeuges vorgeschlagen, wobei bei erkanntem Stillstand des Fahrzeuges Bremskraft zur Realisierung einer Feststellbremse aufgebaut und/oder ein Getriebe in Parkstellung geschaltet wird, wobei die Bremskraft bzw. die Getriebeposition auch dann aufrechterhalten wird, wenn die Versorgungsspannung für die elektrischen Systeme des Fahrzeuges abgeschaltet ist.



150 ... DRIVES WISHES TO "DRIVE OFF"  
164 ... RELEASE PARKING BRAKE SHIFT GEARS  
152 ... ACC ACTIVATED  
154 ... STANDSTILL ?  
156 ... NEAR STANDSTILL ?  
158 ... ACC CONTROL  
160 ... STOPPING FUNCTION  
162 ... ENGAGE PARKING BRAKE SHIFT GEARS — N, P, ACC, OFF








FIG. 2

FIG. 3




FIG. 4




FIG. 4a




FIG. 4b




Fig. 4c




Fig. 4d




Fig. 4e

Declaration and Power of Attorney for National Stage of PCT Patent Application

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled: Method and Arrangement for Ensuring the Standstill of a Vehicle, especially in Combination with a Control of the Speed of the Vehicle, the specification of which was filed as PCT International Application number PCT/DE 99/01389 on May 8, 1999.

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, §1.56(a).

I hereby claim foreign priority benefits under Title 35, United States Code, §119, of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

<u>Prior Foreign Application(s)</u>	<u>Priority Claimed</u>
<u>198 38 885.3</u> (Number)	<u>Federal Republic of Germany</u> (Country)
	<u>27 Aug 98</u> Date Filed
	<u>X</u> Yes
	<u>      </u> No

As a named inventor, I hereby appoint the following attorney to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith:

Walter Ottesen  
Reg. No. 25,544

Direct all telephone calls to Walter Ottesen at telephone no. (301) 869-8950 and address all correspondence to:

Walter Ottesen  
Patent Attorney  
P.O. Box 4026  
Gaithersburg, Maryland 20885-4026

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full name of sole or first inventor, if any Hermann Winner

Inventor's signature X Hermann Winner Date X 14.12.2000  
Residence 76229 Karlsruhe, Federal Republic of Germany DEX  
Country of Citizenship Federal Republic of Germany  
Post Office Address Im Mehl 3, 76229 Karlsruhe  
Federal Republic of Germany

Inventor's signature

Date \_\_\_\_\_

18.12.00

Residence 70563 Stuttgart, Federal Republic of Germany **DEX**

Country of Citizenship Federal Republic of Germany

Post Office Address Schaedleweg 2, 70563 Stuttgart

Federal Republic of Germany

DATE	DESCRIPTION	AMOUNT	BALANCE
1900	Jan 1		100.00
	Feb 1	50.00	150.00
	Mar 1	25.00	175.00
	Apr 1	75.00	250.00
	May 1	100.00	350.00
	Jun 1	150.00	500.00
	Jul 1	200.00	700.00
	Aug 1	250.00	950.00
	Sep 1	300.00	1250.00
	Oct 1	350.00	1600.00
	Nov 1	400.00	2000.00
	Dec 1	450.00	2450.00
1901	Jan 1	500.00	2950.00
	Feb 1	550.00	3500.00
	Mar 1	600.00	4100.00
	Apr 1	650.00	4750.00
	May 1	700.00	5450.00
	Jun 1	750.00	6200.00
	Jul 1	800.00	7000.00
	Aug 1	850.00	7850.00
	Sep 1	900.00	8750.00
	Oct 1	950.00	9700.00
	Nov 1	1000.00	10700.00
	Dec 1	1050.00	11750.00
1902	Jan 1	1100.00	12850.00
	Feb 1	1150.00	14000.00
	Mar 1	1200.00	15200.00
	Apr 1	1250.00	16450.00
	May 1	1300.00	17750.00
	Jun 1	1350.00	19100.00
	Jul 1	1400.00	20500.00
	Aug 1	1450.00	21950.00
	Sep 1	1500.00	23450.00
	Oct 1	1550.00	25000.00
	Nov 1	1600.00	26600.00
	Dec 1	1650.00	28250.00
1903	Jan 1	1700.00	29950.00
	Feb 1	1750.00	31700.00
	Mar 1	1800.00	33500.00
	Apr 1	1850.00	35350.00
	May 1	1900.00	37250.00
	Jun 1	1950.00	39200.00
	Jul 1	2000.00	41200.00
	Aug 1	2050.00	43250.00
	Sep 1	2100.00	45350.00
	Oct 1	2150.00	47500.00
	Nov 1	2200.00	49700.00
	Dec 1	2250.00	51950.00
1904	Jan 1	2300.00	54250.00
	Feb 1	2350.00	56600.00
	Mar 1	2400.00	59000.00
	Apr 1	2450.00	61450.00
	May 1	2500.00	63950.00
	Jun 1	2550.00	66500.00
	Jul 1	2600.00	69100.00
	Aug 1	2650.00	71750.00
	Sep 1	2700.00	74450.00
	Oct 1	2750.00	77200.00
	Nov 1	2800.00	80000.00
	Dec 1	2850.00	82850.00
1905	Jan 1	2900.00	85750.00
	Feb 1	2950.00	88700.00
	Mar 1	3000.00	91700.00
	Apr 1	3050.00	94750.00
	May 1	3100.00	97850.00
	Jun 1	3150.00	101000.00
	Jul 1	3200.00	104200.00
	Aug 1	3250.00	107450.00
	Sep 1	3300.00	110750.00
	Oct 1	3350.00	114100.00
	Nov 1	3400.00	117500.00
	Dec 1	3450.00	120950.00
1906	Jan 1	3500.00	124450.00
	Feb 1	3550.00	128000.00
	Mar 1	3600.00	131600.00
	Apr 1	3650.00	135250.00
	May 1	3700.00	138950.00
	Jun 1	3750.00	142700.00
	Jul 1	3800.00	146500.00
	Aug 1	3850.00	150350.00
	Sep 1	3900.00	154250.00
	Oct 1	3950.00	158200.00
	Nov 1	4000.00	162200.00
	Dec 1	4050.00	166250.00
1907	Jan 1</		